FIG. 159 ADJUSTABLE ROD BEAM CLAMP




MAX REC

LOAD (lbs)

WEIGHT

EACH (lbs)



MATERIAL

SIZE

Material: Carbon steel.

В

FLANGE WIDTH

MIN

MAX

Finish: Plain or electro-galvanized.

Service: Designed to be used in the suspension of a hanger rod from

an I-beam. Recommended for flange widths from 4 inches

minimum to 8 inches maximum.

Approvals: Complies with Federal Specifications WW-H-171-E

(Type# 54), A-A-1192 A (Type# 27), and MSS SP-58 and

SP-69 (Type# 27).

Ordering: Specify rod size, figure number and finish.

³ /8-16	3ga x 1 ¹ / ₄	3 ¹ / ₂			3/8	1	1))))]	0.98	300	
1/2-13	3ga x 1 ¹ / ₂	3 ¹ / ₂	8	2	1/2	15/16	2 ³ /4	1.38	700	
5/8-11	3ga x 1 ³ / ₄	3 ¹ / ₂	*THRE	ADED PI	5/8	7/8		1.86	1000	
3/4		6		3 3/8	3/4	2	4	6.50	1800	

IMPRICABILITY	Project Information	Approval Stamp			
Project:	IN I IN LINDUSTRIAL	Notes:			
Address:	Contractor:	THREADED PRODUCTS			
Date:	Engineer:				
Approved	Approved as Noted Not Approved Not Approved	MINDUCTRIAL			